

On page 7, between lines 2 and 3, please insert --DETAILED DESCRIPTION OF THE INVENTION--;

line 12, please change "socalled" to --so-called--; and

line 26, please change "introduced" to --incorporated--.

On page 10, line 1, please change "Fig. 1 shows" to --Figs. 1a and b show--.

On page 14, line 11, please change "(10)" to --(6)--; and
line 15, please change "(11)" to --(7)--.

On page 15, line 13, please change "Fig. 1" to --Figs. 1a and b--;
line 14, please change "Fig. 2." to --Figs. 2a and b.--; and
line 23, please change "(12)" to --(8)--.

On page 16, line 1, please change "Fig. 2 shows" to --Figs. 2a and b show--; and
line 22, please change "(13)" to --(9)--.

On page 17, line 9, please change "(14)" to --(10)--.

In the Claims

1. (Amended) A method [Method] for detecting [the] modes of a dynamic system with a multiplicity [large number] of modes s_i that each have a set $\alpha(t)$ of characteristic system parameters, in which a time series of at least one system variable $x(t)$ is subjected to modeling so that in each time segment of a predetermined minimum length a predetermined prediction model f_i for a system mode s_i is detected for each system variable $x(t)$, [characterized in that the modeling of the time series is followed by] comprising performing drift segmentation subsequent to said modeling in which, in each time segment in which there is transition of the system from a first system mode s_i to a second system mode s_j , a series of mixed prediction models g_i is detected and produced by linear, paired superimposition of [the] prediction models $f_{i,j}$ of the two system modes $s_{i,j}$.

In Claim 2, line 1, please change "Method" to --The method--.